User Interaction

Sr	Questions	Answers Choice
1	The name, computer suggests that _____ is the most important aspect of computers:	A. computation B. working C. location D. math
2	Which operator is used to assign a value to a variable ?	A. Assignmentoperator B. arithmeticoperator C. logicaloperator D. all of these
3	Which of the following is not a type of operator ?	A. arithmetic operator B. checkoperator C. relationaloperator D. logicaloperator

4	Let the following part of code, what will be the value of variable an after execution:
	int a = 4;
	float b= 2.2;
	a = a * b;
		A. 8.8
		B. 8
		C. 8.2
		D. 8.0

5	Which operator assigns the result of expression on right side to the variable on left side ?	A. == B. = C. * D. ( )
6	Which operator performs division of left operand by the right operand and returns the remainder value after division ?	A. + B. % C. * D. .
7	Which symbol is used to represent the NOT operator ?	
8	Which of the following is used as an assignmentoperator in C language ?	A. = B. == C. + D. ?
9	In C language _____ is used as statement terminator:	A. ; B. : C. , D. "
10	Which operators are used to perform arithmetic operations on data ?	A. assignmentoperator B. arithmeticoperator C. logicaloperator D. relational operators
11	Which operators perform operation on Boolean expressions and produce a Boolean expressions as a result ?	A. logical B. assignment C. arithmetic D. relation
12	Which is a built-in function in C language that takes input from user into the variables ?	A. printf() B. scanf() C. input D. print
13	Which operators are applied over one operand only ?	A. unary B. binary C. ternary D. all of these
14	Escape sequences consists of _____ characters:	A. two B. three C. four D. five
15	Which is used to display data in specific format ?	A. read B. data C. specifiers D. format specifiers
		A. unary

16	Which operators require two operands to perform the operations ?	B. binary C. ternary D. all of these
17	In which function character entered by user does not get displayed on screen ?	A. getch() B. count C. string D. printf
18	A tab stop is collection of _____ spaces:	A. 8 B. 6 C. 7 D. 9
19	Which operator takes two Boolean expression as operands and produces the result true if both of its operands are true ?	
20	Which operator accepts Boolean expression and returns true if at least one of the operands is true ?	