ICS Part 2 Computer Science Chapter 10 Online Test

Sr	Questions	Answers Choice
1	Which of the following is not a valid escape code?	A. \t B. \r C. \y D. \f
2	The function getche( ) is defined in	A. stdio.h B. string.h C. math.h D. conio.h
3	Which of the following format specifiers is used for float data type?	A. %s B. %c C. %d D. %f
4	Which of the following is displayed by printf function?	A. Text B. Constant or values of variable C. A and B D. Graphics
5	The statement printf ("%-10d",n) will display the value of n:	A. Right justified in ten-character space B. Left justified in ten-character space C. Center-justified in ten-character space D. None of these
6	%f is used for:	A. Double B. Float C. Integer D. Short
7	The function used to show the output on screen is	A. Printf() B. Scanf() C. Sqrt() D. Main()
8	Which function is used to input data in C program?	A. scanf B. getch() C. gets() D. All
9	The function that is used to display output on screen is called:	A. printf B. scanf C. pow D. Display
10	In an E-R diagram a rectangle represents	A. Entity B. Arttibute C. Record D. None of them
11	A factor consider when choosing a file organization is	A. Fast data retrieval B. Security C. Efficient storage D. All of them
12	Which of the following is used to define objects and describe their characteristics	A. Attributes B. Relationship C. Both a & b D. None of them
13	A disadvantages of partitioning is	A. Simplicity B. Extra space and update time C. Both a & b D. None of them
14	The general form of format specifier for floating point value:	A. %m.nf B. m.n% C. m%.nf D. m.n%f
		A. Go character

15	getch() stands for:	B. Get character C. Give character D. All
16	Which escape sequence can be used to begin a new line in C?	A. \a B. \b C. \m D. \n
17	Which escape sequence is used to erase a character left to the cursor position?	A. \b B. \del C. \f D. \c
18	Which escape sequence can be used to beep from speaker in c:	A. \a B. \b C. \m D. \n
19	Which of the following is a possible value of flag?	A. - B. + C. Space D. All
20	Which escape sequence can be used to insert a tab in c:	A. \a B. \b C. \t D. \n